

## 2 Megapixel Mini Dome IP Camera

### 6533

Channel Vision's 6533 IP Mini Dome Camera offers superior image quality with a 2 MP CMOS sensor and has the ability to capture images up to 1280x800 pixels. The 6533 is equipped with a built-in web server that allows high quality videos to be viewed in real-time. The application to view the 6533 on an Android, iPhone and iPad is available in the app store. The 6533 comes with a 36 camera CMS that allows users to view all of their cameras in the same window, from anywhere in the world.



## FEATURES

**Power over Ethernet**

**High definition (2 MP CMOS Sensor)**

**Digital Wide Dynamic Range**

**Micro SD card**

**Vandal Proof Dome**

## SPECIFICATIONS\*

\*Specifications subject to change.

### **Hardware**

**CPU:** Arm 9, 32 bit RISC

**RAM:** 128MB

**Flash:** 16MB

**Image Sensor:** 1/4" 2 Megapixel CMOS Sensor

**Sensitivity:** Color: 1.0 Lux @ 30FPS

**Lens Type:** 4.2mm @ F1.6

**Shutter Time:** 1/5 - 1/10,000 sec

**Power Over Ethernet:** Yes, 48V power consumption, max 2.8 Watts

**Power:** 12vDC 170mA (2.04 Watts Max.)

**Operating Temperature:** 14 °F-113 ° (-10 °C - 45 °C)

**Dimensions:** 3.15" in Diameter x 2.64" Height

**I/O:** 1 Digital Input, 1 Digital Output

**Weight:** 11.99 Ounces

### **Network**

**Ethernet:** 10/100 Base-T

**Network Protocol:** HTTP, HTTPS, SNMP, QoS/DSCP, Access list, IEEE, 802.1X, RTSP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, Bonjour

### **Live Viewing**

**OS:** Windows XP, 7, 8, or Macintosh version 10.6 or newer

**Browser:** Microsoft IE 6.0 or newer, Safari, Firefox & Chrome

**Suggested Hardware:** Intel Dual Core 1.66G, RAM: 1024MB, Graphic card: 128MB (Windows)

### **System**

**Video Resolution:** 1280x800 (Max), 1280x720, 640x489, 320x240, 176x144

**Video Adjustments:** Brightness, Contrast, Hue, Saturation, Shutter Speed, Sharpness, AGC, Shutter Speed adjustable, Sense-Up, D-WDR, Flip, Mirror, Noise reduction, DNR