

Elite Series 2 Megapixel Mini Dome IP Camera

SC6533W

The Elite Series 2 MP IP Dome Camera offers the top-quality images with high definition 1080p. Elite series IP cameras feature integration with Control4 Drivers and SDDP, which allows this camera to integrate seamlessly with Control4 systems. The SC533W is equipped with a built-in web server that allows high quality videos to be viewed in real-time using the internet explorer browser. View all of your camers in the same window, from anywhere in the world, using the Channel Vision App.



FEATURES

2 MP CMOS sensor for 1080p High Definition

Compatibility with Control4 Drivers & SDDP

Digital Wide Dynamic Range

Vandal Proof Dome

SPECIFICATIONS*

*Specifications subject to change.

Hardware

CPU: Arm 9, 32 bit RISC

RAM: 128MB

Flash: 16MB

Image Sensor: 1/2.7" CMOS Sensor

Sensitivity: Color: 0.1 Lux (AGC On)

Lens Type: 2.8mm

Power Over Ethernet: Yes, 48V power consumption, max 3.36 Watts

Power: 12vDC max 2.40 Watts

Operating Temperature: 14 °F-113 ° (-10 °C - 45 °C)

Dimensions: 3.15" in Diameter x 2.64" Height

Field of View: 111.10 ° (H) x 65.10 ° (V)

Weight: 11.99 Ounces

Network

Ethernet: 10/100 Base-T

Network Protocol: HTTP, HTTPS, SNMP, QoS/DSCP, Access list,

IEEE, 802.1X, RTSP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, Bonjour

Live Viewing

OS: Windows XP, 7, 8, or Macintosh version 10.6 or newer

Browser: Microsoft IE 6.0 or newer, Safari, Firefox & Chrome

Suggested Hardware: Intel Dual Core 1.66G, RAM: 1024MB, Graphic

card: 128MB (Windows)

System

Video Resolution: 1920x1080 (Max), 1280x720, 640x480, 320x240, 126x144

Video Adjustments: Brightness, Contrast, Hue, Saturation, Noise reduction, DNR Sharpness,

AGC, Shutter Speed adjustable, Sense-Up, D-WDR, Flip, Mirror