

SI-7000 Elite Series Intercom

SI-7000

Channel Vision's SI Elite Series Door Station interfaces with Channel Vision's Telephone Entry Controllers to provide amplified 2-way communication with one or more doors. The SI series door station features your choice of a built-in high definition IP camera or a hidden 960H analog camera, as well as an illuminated door bell button for enhanced visibility at night.

The SI-7000 series now contains Channel Vision's newest circuit board that allows for more clear communication and volume control than previous models.



FEATURES

Compatible with P-0920 and P-0921

Built-in 2 MP IP Camera

New circuit board provides enhanced 2-way communication

Illuminated door bell button for visibility at night

SPECIFICATIONS *

*Specifications subject to change.

Speaker

Size (mm): 50

Depth (in.): 1.5"

Impedance: 8 Ohms

Power Peak (W): 0.2

Frequency Range: 500 Hz - 4.5 kHz

Dimensions

Rbox: 4"L x 4"W x 7.47"H*

Door Plate: 4.5" x 7.9"

PCB Surface: Waterproof Silicon protected

SI Series Doorplate Surface: Solid Brass, coated & protected

Button Color: Blue LEDs

IP Camera

Total Pixels: 1920 x 1080p

Image Sensor: 1/2.7" CMOS Sensor

IP Camera Hardware

CPU: Arm 9, 32 bit RISC

RAM: 128MB

Flash: 16MB

Sensitivity: 1.0 Lux @ 30fps

Lens Type: 2.8mm Fixed Lens

Power Over Ethernet: Yes, 48V power consumption, max 3.36 Watts

Power: 12vDC max 2.40 Watts

Operating Temperature: 14 °F-113 ° (-10 °C - 45 °C)

Dimensions: 3.15" in Diameter x 2.64" Height

Field of View: 111.10 ° (H) x 65.10 ° (V)

Weight: 11.99 Ounces

*Rbox not sold separately